

General Features

- Supports latest Intel & AMD processors
- Supports Vista System
- MTBF > 100,000 hours @25°C
- Supports Serial ATA interface
- Over Power Protection
- Over Voltage Protection
- Short Circuit Protection
- RoHS compliant

Power Distribution

Dimension	W150 x L140 x H86mm
Specification	ATX12V
Input Voltage	100~240V (90~264Vac)

Model	+3.3V	+5V	+12V1	+12V2	-12V	+5Vsb	Total Power
S12II-330	18A	20A	17A	17A	0.8A	2.5A	330W
	120W		288W		9.6W	12.5W	
S12II-380	20A	20A	17A	17A	0.8A	2.5A	380W
	130W		324W		9.6W	12.5W	
S12II-430	20A	20A	17A	17A	0.8A	2.5A	430W
	130W		360W		9.6W	12.5W	
S12II-500	20A	24A	17A	17A	0.8A	2.5A	500W
	130W		408W		9.6W	12.5W	



Wire Configuration

Cable	Main Power (20 / 24P)	ATX12V (4P)	EPS12V (8P)	Peripheral (4P)	SATA	FDD(MP) (Y-adapter)	PCI-E (6P)	PCI-E (6+2P)
S12II-330	1	1	0	6	4	2	1	0
S12II-380	1	1	0	6	4	2	1	0
S12II-430	1	1	1	6	4	2	2	0
S12II-500	1	1	1	9	6	2	1	1



specification may change without prior notice



Green Innovation Powers Your Life

S12II

SILENT 12CM FAN SERIES

The New Standard for
Silent Power Efficiency



www.seasonic.com

Headquarters

tel: +886-2-2659-0338

fax: +886-2-2659-0530

e-mail: sales@seasonic.com.tw



Seasonic
Since 1975



