





### Special Features


- 80PLUS<sup>®</sup> Bronze Certified High Efficiency
- Highly Reliable 105°C Japanese Brand Capacitor
- Ample +12V Outputs
- Active Power Factor Correction [99% PF Typical]
- Double Forward Converter Design
- Smart & Silent Fan Control [S<sup>2</sup>FC]
- 12cm Ball Bearing Cooling Fan
- Soft-Mount Rubber Cushions
- Universal Video Card Support
- All-in-One DC Cabling Design
- Detachable Modular Cables
- Patented Easy Swap Connector
- Universal AC Input [Full Range]
- Ultra Ventilation [Honeycomb Structure]
- 3 Year Warranty



Honeycomb Structure



Flexible Modular Cable



High Quality 105°C Cap

### Power Distribution

Model	+3.3V	+5V	+12V comb.	-12V	+5Vsb	Total Power
M12II-620 Bronze	24A	24A	48A	0.8A	2.5A	620W
	130W		576W	9.6W	12.5W	
M12II-520 Bronze	24A	24A	40A	0.8A	2.5A	520W
	130W		480W	9.6W	12.5W	

### Wire Configuration

Connector	Main Power (24P / 20P) 550mm	EPS12V/ATX12V (8P / 4P) 550mm	EPS12V (8P) 550mm	Peripheral (4P) 550mm	SATA	FDD (Y-adapter) (4P)	PCI-E (6P) 550mm	PCI-E (8P / 6P) 600mm
M12II-620 Bronze	1	1	1	6	9	2	1	1
M12II-520 Bronze	1	1	1	6	6	2	1	1

Wire length within +/-5% tolerance

### Safety & EMI / EMC



**Green Innovation Powers Your Life**



Specifications may change without prior notice

